

AD-A252 216



DDPOPHM/USA/ODD/NADTR92107

2

PERFORMANCE ORIENTED PACKAGING TESTING

OF

MK 663 MOD 0 BLASTING CAP CONTAINER

FOR

PACKING GROUP II

SOLID HAZARDOUS MATERIALS

BY:

KERRY J. LIBBERT

MECHANICAL ENGINEER

Performing Activity:
Crane Division
Naval Surface Warfare Center
Crane, Indiana 47522-5000

DTIC
ELECTE
JUN 29 1992
S D

MAY 1992

FINAL

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED.

Sponsoring Organization:
Naval Weapons Station Earle
Program Management Office - Code 50
Colts Neck, New Jersey 07722-5000

92-16921



92 6 20 038

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<i>P-1</i>	

Prepared by:

K. J. Libbert
K. J. Libbert

Reviewed by:

R. F. Sanders
R. F. Sanders



Reviewed by:

J. W. Puckett
J. W. Puckett

Approved by:

D. N. Montgomery
D. N. Montgomery

REPORT DOCUMENTATION PAGE			Form Approved OMB No 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 5-92	3. REPORT TYPE AND DATES COVERED Final		
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of MK 663 MOD 0 Blasting Cap Container for Packing Group II Solid Hazardous Materials		5. FUNDING NUMBERS		
6. AUTHOR(S) Kerry J. Libbert				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Crane Division Naval Surface Warfare Center Code 4045 Crane, IN 47522-5040		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Crane Division Naval Surface Warfare Center Code 4027 Crane, IN 47522-5040		10. SPONSORING/MONITORING AGENCY REPORT NUMBER DODPOPHM/USA/DOD/ NADTR 92107		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unlimited Distribution		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) The MK 663 MOD 0 Blasting Cap Container was tested for conformance to Performance Oriented Packaging criteria established by the United Nations Recommendations on the Transport of Dangerous Goods and Code of Federal Regulations 49 CFR. The container was tested with a gross weight of 15.4 pounds (7 kilograms) and met all requirements.				
14. SUBJECT TERMS Performance Oriented Packaging MK 663 MOD 0 Blasting Cap Container		15. NUMBER OF PAGES 6		
		16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UI.	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines** to meet **optical scanning requirements**.

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered
State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s) Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es) Self-explanatory.

Block 8. Performing Organization Report Number Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es) Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number (If known)

Block 11. Supplementary Notes Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement
Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages Enter the total number of pages.

Block 16. Price Code Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

INTRODUCTION

The MK663 Mod 0 Blasting Cap Container was tested to ascertain whether the container would meet the requirements of Performance Oriented Packaging (POP) as specified by the United Nations Recommendations on the Transport of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test was also conducted in accordance with the rulings specified by the Department of Transportation Performance Oriented Packaging Standards, 49 CFR Part 106 et al. Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations. The objectives were to evaluate the adequacy of the container in protecting and retaining the blasting caps when secured with appropriate dunnage.

The MK663 Mod 0 Blasting Cap Container is a cylindrical stainless steel container with a screw-on aluminum cap used for shipment and storage of ten M6 or M7 blasting caps. The container is shown in Figure 1.

TESTS PERFORMED

1. Drop Test

This test was performed in accordance with ST/SG/AC.10/1, Chapter 9, Paragraph 9.7.3. The container was tested first as a box, then as a drum. Five containers were used during the test series for a box, one for each drop. The drop height was 1.2 meters and the drop sequence was as follows:

- a. Flat on Bottom
- b. Flat on Top
- c. Flat on Long Side
- d. Flat on Short Side
- e. On a Corner


The test series for a drum required six containers, three for each drop. The drop height was 1.2 meters and the drop sequence was as follows:

- a. Bottom Chime
- b. Edge of Lid

The tests were performed at ambient temperature ($70^{\circ} + 20^{\circ}\text{F}$). The contents of the container should be retained within its packaging and exhibit no damage liable to affect safety during transport.

2. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, Chapter 9, Paragraph 9.7.6. Three different containers were used, each with a stack weight of 650 pounds. This weight represents the load superimposed on the bottom container of a sixteen-foot stack of MK663 containers weighing 15.4 pounds each.



The test was performed for 24 hours. After the allowed time, the weight was removed and the container examined. Any leakage, deterioration, or distortion which could adversely affect transport or reduce its strength or cause instability in stacks of packages is cause for rejection.

3. Base Level Vibration Test

This test was performed in accordance with the Federal Register/Vol 56, No. 245/Friday, December 20, 1991/Rules and Regulations. Three sample containers were loaded with sand and closed as for shipment. Each container was placed on a vibrating platform that had a vertical double-amplitude (peak-to-peak displacement) of one inch. The packages were constrained horizontally to prevent them from falling off the platform, but were free to move vertically, bounce and rotate. The test was performed for one hour at a frequency that caused each point of the container bottom to be raised from the platform to such a degree that a 1.6mm thick metal strip could be passed between the bottom of any package and the platform.

PASS/FAIL (UN CRITERIA)

The criteria for passing the drop test is outlined in Paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retained by an inner packaging or inner receptacle (e.g., a plastic bag), even if the closure is no longer sift-proof".

The criteria for passing the stacking test is outlined in Paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages".

PASS/FAIL (FEDERAL REGISTER CRITERIA)

The criteria for passing the Base Level Vibration Test is outlined in the Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations and states the following: "Immediately following the period of vibration, each package shall be removed from the platform, turned on its side and observed for any evidence of leakage. A packaging passes the vibration test if there is no rupture or leakage from any of the packages. No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength."

TEST RESULTS

1. Drop Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Base Level Vibration Test

Satisfactory.

DISCUSSION

1. Drop Test

After each drop the container was inspected for any damage which would be cause for rejection. The only container damaged was the one subjected to the drop on top, which bent the handle, but no drop caused any spillage of contents.

2. Stacking Test

Three containers were individually tested. Each container was visibly inspected after the 24-hour period was over. There was no leakage, distortion, or deterioration to the container as a result of this test.

3. Base Level Vibration Test

Immediately following the vibration test, each container was removed from the platform, turned on its side and observed for any evidence of leakage. The lids of two of the containers were loosened by approximately 1/8 of a turn during the test, but remained fastened. There was no evidence of leakage of contents.

REFERENCE MATERIAL

United Nation's "Recommendations on the Transport of Dangerous Goods", ST/SG/AC.10/1, Revision 6

Department of Transportation Performance Oriented Packaging Standards, 49 CFR Part 106 et al. Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations

DISTRIBUTION LIST

Commander
Crane Division
Naval Surface Warfare Center
Code 4045 and Code 4027
Crane, IN 47522-5000

Commanding Officer
Naval Weapons Station Earle
Code 50 and Code 50232
Colts Neck, NJ 07722-5000

Defense Technical Information Center (2 copies)
ATTN: DTIC/EDAC (Virginia Guidi)
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Commander
U.S. Army Armament, Research, Development and Engineering
Center
SMCAR-ESK
Rock Island, IL 61299-7300

Defense General Supply Center
DDRV-TMPA (Dave Gay)
Richmond, VA 23297-5000

DATA SHEET

CONTAINER: MK663 Blasting Cap Container		POP MARKING: <div style="display: inline-block; border: 1px solid black; border-radius: 50%; padding: 2px; text-align: center;">u n</div> 4A1/Y7/S/** USA/DOD/NAD
Type: 4A1		UN Code: 1.1B
Specification Number: 53711-5206200		Material: Stainless Steel
Gross Weight: 7.0 kg (15.4 pounds)	Dimensions: .30 m L x .11 m DIA (11.9" L x 4.5" DIA)	
Closure (Method/type): Screw-on cap		Tare Weight: 5.2 kg (11.5 pounds)
Additional Description: Cylindrical stainless steel body with aluminum cap.		
PRODUCTS: M6 Blasting Cap, M130, 1375-00-756-1865 M7 Blasting Cap, M131, 1375-00-283-9440		
Proper Shipping Name: M6- Detonators, Electric M7- Detonators, Non-electric		
United Nations Number: M6- 0030 M7- 0029		
United Nations Packing Group: II		
Physical State: Solid		
Amount Per Container: 10		
Net Weight: Varies		
TEST PRODUCT: Name: Sand Physical State: Solid		
Size: N/A		
Quantity: N/A		
Dunnage: None Gross Weight: 7.0 kg (15.4 lbs.)		